

型号	主要尺寸										额定载荷		重量
Bearing No.	Bore内径		Outer Diameter外径		Width宽				Radius半径		Load Rating(KN)		Weight
	d		D		B		r		Dynamic	Static			
	mm	inch	mm	inch	open	sealed	min		Cr动	Cor静			
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	Cr动	Cor静	(kg)
1601	4.762	0.188	17.462	0.688	6.35	0.25	7.938	0.313	0.3	0.012	1.511	0.724	0.005
1602	6.35	0.250	17.462	0.688	6.35	0.25	7.938	0.313	0.3	0.012	1.511	0.724	0.006
1603	7.938	0.313	22.225	0.875	7.144	0.281	8.731	0.281	0.3	0.012	2.547	1.342	0.011
1604	9.525	0.375	22.225	0.875	7.144	0.281	8.731	0.281	0.38	0.015	2.547	1.342	0.013
1605	7.938	0.313	23.019	0.906	7.938	0.313	7.938	0.313	0.03	0.012	2.547	1.342	0.014
1606	9.525	0.375	23.019	0.906	7.938	0.313	7.938	0.313	0.3	0.012	2.547	1.342	0.015
1607	11.113	0.438	23.019	0.906	7.938	0.313	7.938	0.313	0.3	0.012	3.556	1.938	0.016
1614	9.525	0.375	28.575	1.125	9.525	0.375	9.525	0.375	0.3	0.012	3.921	2.245	0.035
1615	11.113	0.438	28.575	1.125	9.525	0.375	9.525	0.375	0.3	0.012	3.921	2.245	0.034
1616	12.7	0.5	28.575	1.125	9.525	0.375	9.52	0.375	0.3	0.012	3.921	2.245	0.03
1620	11.113	0.438	34.925	1.375	11.113	0.438	11.113	0.438	0.3	0.012	5.88	3.49	0.05
1621	12.7	0.5	34.925	1.375	11.113	0.438	11.113	0.438	0.3	0.012	5.88	3.49	0.048
1622	14.288	0.563	34.925	1.375	11.113	0.438	11.113	0.438	0.6	0.025	5.88	3.49	0.046
1623	15.875	0.625	34.925	1.375	11.113	0.438	11.113	0.438	0.6	0.025	5.8	3.49	0.04
1628	15.875	0.625	41.275	1.625	12.7	0.5	12.7	0.5	0.6	0.025	7.232	4.45	0.072
1630	19.05	0.75	41.275	1.625	12.7	0.5	12.7	0.5	0.6	0.025	7.232	4.45	0.065
1633	15.875	0.625	44.45	1.75	12.7	0.5	12.7	0.5	0.6	0.025	7.232	4.45	0.092
1635	19.05	0.75	44.45	1.75	12.7	0.5	12.7	0.5	0.6	0.025	7.232	4.45	0.085